



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL Semi Power 10W-30

Description of the

TIPP-OIL Semi Power 10W-30 is a semi-synthetic high-performance engine oil for passenger cars.

Petrol and diesel engines with and without turbocharging and direct injection. Extended oil change intervals according to manufacturer's instructions.

TIPP-OIL Semi Power 10W-30 is characterized by excellent cold start characteristics, minimization of fuel consumption, friction and wear.

TIPP-OIL Semi Power 10W-30 is a reliable and heavy-duty engine oil.

Instructions for use

TIPP-OIL Semi Power 10W-30 is ideally suited for year-round use in all modern passenger car petrol and diesel engines.

TIPP-OIL Semi Power 10W-30 is used in engines with the specified specifications. The operating instructions of the vehicle and engine manufacturers must be observed.

Quality Classification

specifications

API SN/SM

ILSAC GF-5

TIPP-OIL Semi Power 10W-30 is proven in practice and tested in units with filling regulations:

Chrysler MS-6395 Daewoo

Fiat 9.55535-CR1 Daihatsu

GM 6094M Honda



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

Hyundai

Isuzu

KIA

Mazda

Mitzubishi

Nissan

SsangYong

Subaru

Suzuki

Toyota

#### Features & Benefits

Excellent cold start properties, even at low temperatures

A very stable viscosity behaviour, shear stability

Reduction of fuel consumption under all operating conditions

Very good detergent and dispersing properties

Neutrality towards sealing materials

Low evaporation tendency, thus low oil consumption

Extensive protection against wear, corrosion and foam formation

Extended oil change intervals protect natural resources



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailadress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

#### Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 63,9 MM<sup>2</sup>/S DIN ISO 51562-2

kinematic viscosity at 100°C 10.1 MM<sup>2</sup>/S DIN ISO 51562-2

viscosity index 144 DIN ISO 2909

visual appearance YELLOWBROWN

density at 15°C 861 KG/M<sup>3</sup> DIN EN ISO 12185

Pour Point -39 CELSIUS ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

22.08.2018 02:00:15

