



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL SEMiS 5W-30

Description of the

TIPP-OIL SEMiS 5W-30 is a semi-synthetic low-viscosity engine oil for passenger car petrol and diesel engines with and without turbocharging and direct injection. Allows extended oil change intervals according to manufacturer's instructions.

TIPP-OIL SEMiS 5W-30 is characterized by excellent cold start properties, minimization of fuel consumption, friction and wear.

TIPP-OIL SEMiS 5W-30 is a reliable and heavy-duty engine oil.

Instructions for use

TIPP-OIL SEMiS 5W-30 is ideally suited for year-round use in all modern passenger car petrol and diesel engines.

TIPP-OIL SEMiS 5W-30 is used in engines with the specified specifications. The operating instructions of the vehicle and engine manufacturers must be observed.

Quality Classification

specifications

API SL/CF ACEA A3/B4

TIPP-OIL SEMiS 5W-30 is proven in practice and tested in units with filling regulations:

MB 229.3 BMW Longlife-98

VW 502 00/505 00



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

#### Features & Benefits

Excellent cold start properties even at low temperatures below -25°C  
A very stable and excellent viscosity behaviour, shear stability  
Fuel savings under all operating conditions  
Very good detergent and dispersing properties  
Neutrality towards sealing materials  
Low evaporation tendency, thus low oil consumption  
Extensive protection against wear, corrosion and foam formation.  
Catalyst suitability  
Extended oil change intervals protect natural resources

#### Technical characteristics

Properties Data Unit Test according to  
kinematic viscosity at 40°C 70.9 MM<sup>2</sup>/S DIN ISO 51562-2  
kinematic viscosity at 100°C 12.2 MM<sup>2</sup>/S DIN ISO 51562-2  
viscosity index 170 DIN ISO 2909  
visual appearance YELLOWBROWN  
density at 15°C 855 KG/M<sup>3</sup> DIN EN ISO 12185  
Pour Point -39 CELSIUS ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

03.10.2018 02:00:08



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

