



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL Super Truck 40

Description of the

TIPP-OIL Super Truck 40 is an HD engine oil, highly alloyed with synthetic additives, suitable for truck diesel engines also with turbocharging.

With TIPP-OIL Super Truck 40, a reliable and highly resilient engine oil has been developed that also offers safety reserves.

Instructions for use

TIPP-OIL Super Truck 40 is suitable for year-round use in diesel engines and commercial vehicle engines with and without turbocharging.

TIPP-OIL Super Truck 40 is used in engines with the specified specifications. The operating instructions of the engine manufacturer must be observed.

Quality Classification

specifications

ACEA E2-96/B4-04 API CF-4/SG

TIPP-OIL Super Truck 40 is proven in practice and tested in units with filling regulations:

Allison C-4

Caterpillar TO-2

Deutz DQC I-02

MAN 270



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

MB 228.0/235.12

MIL-L-2104 D

MTU Type 1

ZF TE-ML 02H/04A/04B

Features & Benefits

A stable and excellent viscosity behaviour

Good detergent and dispersing properties

Neutrality towards sealing materials

Extensive protection against wear, corrosion and foam formation

catalyst suitability

Very good shear stability

Prevention of black sludge formation

High safety reserves even under limit lubrication conditions

High oxidation stability

Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 149.0 MM²/S DIN ISO 51562-2

kinematic viscosity at 100°C 14.2 MM²/S DIN ISO 51562-2

viscosity index 92 DIN ISO 2909

visual appearance YELLOWBROWN

density at 15°C 897 KG/M³ DIN EN ISO 12185

Pour Point -18 CELSIUS ASTM D 7346



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In case of any problems, please request technical advice.

