



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL Super Truck Turbo SAE 40

Description of the

TIPP-OIL Super Truck Turbo 40 is an HD engine oil, highly alloyed with synthetic additives, suitable for truck diesel engines also with turbocharging.

TIPP-OIL Super Truck Turbo 40 is a reliable and heavy-duty engine oil.

Instructions for use

TIPP-OIL Super Truck Turbo 40 is suitable for year-round use in diesel engines and commercial vehicle engines with and without turbocharging.

TIPP-OIL Super Truck Turbo 40 is used in engines with the specified specifications. The operating instructions of the engine manufacturer must be observed.

Quality Classification

specifications

ACEA A3/B3

ACEA E7/E5/E3

API CI-4/CF-2/SL

TIPP-OIL Super Truck Turbo 40 is proven in practice and tested in units with filling regulations:

Caterpillar TO-2

Deutz DQC II-10

MAN 270/M 3275-2

MIL-L-2104 E



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

MTU Type 2

Volvo VDS

MB 228.2

#### Features & Benefits

A stable and excellent viscosity behaviour

Good detergent and dispersing properties

Neutrality towards sealing materials

Extensive protection against wear, corrosion and foam formation

catalyst suitability

Very good shear stability

Prevention of black sludge formation

High safety reserves even under boundary lubrication conditions

High oxidation stability

#### Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 127.0 MM<sup>2</sup>/S DIN ISO 51562-2

kinematic viscosity at 100°C 13.8 MM<sup>2</sup>/S DIN ISO 51562-2

viscosity index 105 DIN ISO 2909

visual appearance YELLOWBROWN

density at 15°C 889 KG/M<sup>3</sup> DIN EN ISO 12185

Pour Point -30 CELSIUS ASTM D 7346



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

17.07.2018 15:28:38

