



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL Super Truck Turbo SAE 50

Description of the

TIPP-OIL Super Truck Turbo 50 is an HD engine oil, highly alloyed with synthetic additives, suitable for petrol and diesel engines, even with turbocharging.

TIPP-OIL Super Truck Turbo 50 is a reliable and heavy-duty engine oil.

Instructions for use

TIPP-OIL Super Truck Turbo 50 is suitable for year-round use in petrol and diesel engines as well as commercial vehicle engines with and without turbocharging.

TIPP-OIL Super Truck Turbo 50 is used in engines with the specified specifications. The operating instructions of the engine manufacturer must be observed.

Quality Classification

specifications

ACEA A3/B3

ACEA E7/E5/E3

API CI-4/CF-2/SL

TIPP-OIL Super Truck Turbo 50 is proven in practice and tested in units with filling regulations:

Caterpillar TO-2

Deutz DQC II-10

MAN 270/M 3275-2



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailadress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

MIL-L-2104 E

MTU Type 2

Volvo VDS

MB 228.2

Features & Benefits

A stable and excellent viscosity behaviour

Good detergent and dispersing properties

Neutrality towards sealing materials

Extensive protection against wear, corrosion and foam formation

catalyst suitability

Suitable for passenger cars as well as commercial vehicles, agricultural and construction machinery

Prevention of black sludge formation

High safety reserves even under boundary lubrication conditions

High oxidation stability

Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 207.0 MM²/S DIN ISO 51562-2

kinematic viscosity at 100°C 18.5 MM²/S DIN ISO 51562-2

viscosity index 99 DIN ISO 2909

visual appearance YELLOWBROWN

density at 15°C 901 KG/M³ DIN EN ISO 12185



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

Pour Point -24 CELSIUS ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

17.07.2018 15:28:21

