



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL Truck Gear LongLife 75W-80

Description of the

TIPP-OIL Truck Gear LongLife 75W-80 is a fully synthetic, high performance, low friction transmission oil with a special additive and inhibition that ensures perfect transmission performance.

TIPP-OIL Truck Gear LongLife 75W-80 has been specially formulated to meet the requirements of

commercial vehicle manual transmission and is excellently suited for very high mechanical and thermal loads, even at the longest oil change intervals.

Instructions for use

TIPP-OIL Truck Gear LongLife 75W-80 is a high performance transmission oil for the supply of synchronized commercial vehicle manual transmissions,

especially if oils of the type Volvo 97307 or Volvo 97305 are required (see recommendations in the manufacturer's instructions). The shifting comfort is significantly increased. Extreme

Oil change intervals of up to 500,000 km according to manufacturer specifications reduce maintenance costs and increase efficiency.

Quality Classification

specifications

API GL-4



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

Recommendation

MIL-L-2105 MIL-L-2105
MAN 341 Type Z4 VOLVO 97307
ZF TE-ML 01L, 02L, 16K

TIPP-OIL Truck Gear LongLife 75W-80 is field-proven and tested in units with filling regulations:

MAN 341 Type E3
VOLVO 97305
VOLVO 97318
DAF
EATON (Extended drain) / IVECO / RENAULT
MAN 341 Type V-R

Features & Benefits

High additive reserves for extended oil change intervals according to manufacturer's instructions
Best wear protection and best gear efficiency
Fuel savings even in short-distance operation, even at low outside temperatures
A stable lubricating film even under high loads
Exceptionally good corrosion protection and good compatibility with non-ferrous metals
High oxidative resistance prevents oil thickening and deposits
Excellent dirt carrying capacity, even after very long oil change intervals
Extreme shear stability, even after very long periods of use
Very strong protection against rust, corrosion and foam formation



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

Excellent EP properties

Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 100°C 9.400 MM²/S DIN ISO 51562-2

viscosity index 156 DIN ISO 2909

appearance YELLOW visual

density at 15°C 855,0 KG/M³ DIN EN ISO 12185

Pour Point -42 °C ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes without notice. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

13.09.2018 02:00:10



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

