



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL Ultra Excellence 5W-30

Description of the

TIPP-OIL Ultra Excellence 5W-30 is a synthetic Low SAPS fuel-efficient engine oil for passenger car gasoline and diesel engines. It is particularly suitable for state-of-the-art diesel engines with particulate filters.

TIPP-OIL Ultra Excellence 5W-30 is characterized by excellent cold start properties, minimization of fuel consumption, friction and wear.

TIPP-OIL Ultra Excellence 5W-30 provides measurable fuel savings and emission reduction through reduced HTHS viscosity.

TIPP-OIL Ultra Excellence 5W-30 helps to protect the environment. Extended oil change intervals according to manufacturer's instructions.

Instructions for use

TIPP-OIL Ultra Excellence 5W-30 is a synthetic low friction engine oil, which was developed especially for diesel engines with particulate filter.

TIPP-OIL Ultra Excellence 5W-30 is suitable for petrol and diesel engines in passenger cars and vans with and without turbochargers.

Quality Classification

specifications

ACEA C1/C2

Jaguar Land Rover STJLR.03.50055



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

Jaguar Land Rover STJLR.03.5005

TIPP-OIL Ultra Excellence 5W-30 is proven in practice and tested in units with filling regulations:

Ford WSS-M2C934-A/B Mazda

#### Features & Benefits

Excellent cold start properties even at low temperatures below -30°C

The function of the hydraulic plungers is guaranteed at all temperatures.

Fuel savings under all operating conditions

A safe lubricating film at high operating temperatures

Neutrality towards sealing materials

Extensive protection against wear, corrosion and foam formation.

Low tendency to evaporation, thus low oil consumption.

Extended oil change intervals protect natural resources

Low SAPS = reduced sulfated ash, phosphorus and sulfur

#### Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 54,400 MM<sup>2</sup>/S DIN ISO 51562-2

kinematic viscosity at 100°C 10,100 MM<sup>2</sup>/S DIN ISO 51562-2

viscosity index 175 DIN ISO 2909

visual appearance YELLOWBROWN

density at 15°C 847,0 KG/M<sup>3</sup> DIN EN ISO 12185

Pour Point -39 CELSIUS ASTM D 7346



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailadress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

28.09.2018 02:00:08

