



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL Uni Performance 5W-30

Description of the

TIPP-OIL Uni Performance 5W-30 is based on excellent base oils and additives and is a synthetic fuel-saving "Low SAPS" truck engine oil. This engine oil is particularly suitable for diesel engines under the most severe operating conditions and weather conditions. It is also suitable for use in EURO 4 and EURO 5 engines in combination with low-sulphur diesel fuel, for use in engines with or without particle filter, exhaust catalyst.

TIPP-OIL Uni Performance 5W-30 prevents a high cold start wear, because it is very resistant to the high temperature of the engine.

cold viscosity at very low temperatures ensures that all lubrication points are supplied as quickly as possible. It also has a high temperature viscosity, which reduces friction losses and wear.

Instructions for use

TIPP-OIL Uni Performance 5W-30 is a Low SAPS high-performance commercial vehicle engine oil for EURO 4 and EURO 5 engines that can be used all year round.

TIPP-OIL Uni Performance 5W-30 is suitable for oil change intervals of up to 100,000 km according to manufacturer specifications.

Quality Classification

specifications

JASO DH-2

ACEA E6/E7/E9 API CJ-4/SN



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

TIPP-OIL Uni Performance 5W-30 is field-proven and tested in units with filling regulations:

Caterpillar ECF-3

Cummins CES 20078/20081

DAF HP-2

DDC 93K218

Deutz DQC-IV-10 LA

IVECO 18-1804 TLS E6

Mack EO-O Premium Plus

MAN M 3677/M 3477/M 3277/M 3271-1

MB 228.51/228.31/226.9

MTU Type 3.1

Renault VI RLD-3/RXD/RGD

Scania LDF-4

Volvo CNG

Volvo VDS-4

Features & Benefits

Safe cold start behaviour

High wear protection

Very good oxidation resistance

Low fuel consumption

Detergent properties and dispersing power



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

Low content of sulfated ash, phosphorus & sulfur

High temperature stable and high viscosity

Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 70.8 MM²/S DIN ISO 51562-2

kinematic viscosity at 100°C 12.2 MM²/S DIN ISO 51562-2

viscosity index 170 DIN ISO 2909

visual appearance YELLOWBROWN

density at 15°C 851 KG/M³ DIN EN ISO 12185

Pour Point -42 CELSIUS ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

25.09.2018 02:00:02



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

