



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL WIV-Multi LL 5W-30

Description of the

TIPP-OIL WIV-Multi LL 5W-30 is a synthetic low-friction engine oil for passenger cars, petrol and diesel engines.

Diesel engines with and without turbocharging and direct injection. Minimization of friction, Wear and fuel consumption, excellent cold start characteristics. Extended oil change intervals according to manufacturer's instructions.

TIPP-OIL WIV-Multi LL 5W-30 extends the service life of the diesel particulate filter by reducing the concentration of ash-forming particles in the exhaust gas. Reduces the emission of harmful emissions into the environment. Provides greater safety through sustained high engine protection. Due to its formulation with special base oils, it achieves a high viscosity index.

Instructions for use

TIPP-OIL WIV-Multi LL 5W-30 is ideally suited for energy-saving year-round use in modern petrol and diesel engines.

TIPP-OIL WIV-Multi LL 5W-30 is suitable for extended oil change intervals and extends the service life of the particulate filter. The operating instructions of the vehicle and engine manufacturers must be observed.

Quality Classification

specifications

API SN ACEA C3



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

Recommendation

VW 504 00/507 00

VW 504 00/507 00 MB release 229.51

TIPP-OIL WIV-Multi LL 5W-30 is proven in practice and tested in units with filling regulations:

BMW Longlife-04

Porsche C30

Fiat 9.55535-S3

MB 229.31

Features & Benefits

Excellent cold start properties even at low temperatures below -25°C

Extremely stable and excellent viscosity behavior, shear stability

Fuel savings under all operating conditions

Safe lubricating film at high operating temperatures

Neutrality towards sealing materials

Low evaporation tendency, thus low oil consumption

Excellent protection against wear, corrosion and foam formation.

Catalyst suitability

Extended oil change intervals protect natural resources



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 71.3 MM²/S DIN ISO 51562-2

kinematic viscosity at 100°C 12.1 MM²/S DIN ISO 51562-2

viscosity index 167 DIN ISO 2909

appearance YELLOW visual

density at 15°C 853 KG/M³ DIN EN ISO 12185

Pour Point -42 °C ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In case of any problems, please request technical advice.

17.07.2018 02:01:05

