



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIP-OIL ATF 5/4 HP

ATF 5/4 HP is designed on the basis of hydrocrack oils and PAO with a special additive and inhibition, which guarantee a perfect function of the automatic transmission.

ATF 5/4 HP is a modern generation ATF (Automatic Transmission Fluid) for all 4- and 5-speed automatic transmissions from ZF. Guarantees maximum wear protection in every operating condition. ATF 5/4 HP has a neutral yellow color.

Application note:

ATF 5/4 HP is suitable for use in automatic transmissions of the ZF Series 4 HP (4HP20, 4HP22, 4HP24) and 5HP (5HP18, 5HP19, 5HP24, 5HP30). Maintenance-free filling under normal operating conditions.

Specifications:

Other specifications

Tried and tested in practice in units with filling regulations:

Alfa Romeo 20HP 14891900, ATF LA 2634, ATF LT 71141, BMW 8322 9407765, BMW 8322 9407807, Citroën/Peugeot AL4 PR 9736.22, Jaguar JLM 20237, Land Rover STC4863, Mercedes A 0019892203, Porsche 999.917.547.00, Renault DP0, VW/Audi G052162 A1/ A2/ A6, VW TL 52

Reliable protection against wear, corrosion and foam formation:

Reliable protection against wear, corrosion and foam formation

High and stable viscosity index

Good lubricating properties even at low temperatures in winter



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

Very good oxidation stability

Coordinated coefficient of friction properties

High thermal and oxidative stability

Excellent cooling capacity

Properties Data Unit Test according to

Viscosity at 100°C 7.100 MM<sup>2</sup>/S DIN ISO 51562-2

Viscosity index 177 DIN ISO 2909

Colour Yellow visual

Density at 15°C 850 KG/M<sup>3</sup> DIN EN ISO 12185

Pourpoint -51 °C ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In case of any problems, please request technical advice.



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

