



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL Dexron III G Red ATF

Dexron III G is designed on the basis of hydrocrack oils and PAO with a special additive and inhibition. Dexron III G has been specially developed for the specified specifications and applications. Fulfills a maximum of lubrication and wear protection through special additives. Dexron III G is a universal ATF (Automatic Transmission Fluid) of the latest generation for all automatic transmissions with and without controlled torque converter lock-up clutch (so-called GKÜB = transmission-clutch lock-up) for which transmission fluids of type Dexron III G are prescribed.

Application note:

Dexron III G is especially suitable for use in gearboxes with ATF Dexron III G specification. It is recommended to rinse with Dexron III G before the final filling with Dexron III G is carried out. The operating instructions of the vehicle and engine manufacturers must be observed.

Specifications:

Other specifications

Tried and tested in practice in units with filling regulations:

Ford M2C195-A, GM Dexron III G, MAN 339 Type Z-1/V-1, MB 236.1, 236.5, MERCON, VOITH H55.6335 (G607), ZF TE-ML 02F, 03D, 04D, 09, 11B, 14A, 17C

Properties. Reliable protection against wear, silting, foaming and corrosion:

Reliable protection against wear, silting, foaming and corrosion

Very high viscosity index



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

Problem-free at low temperatures

Very low yield point

Has very good oxidation stability

Well matched coefficient of friction properties

Neutral behaviour towards sealing materials

Neutral behaviour through inhibition against non-ferrous metals

Properties Data Unit Test according to

Viscosity at 100°C 7.300 MM<sup>2</sup>/S DIN ISO 51562-2

Viscosity index 181 DIN ISO 2909

Color Red visual

Density at 15°C 851.0 KG/M<sup>3</sup> DIN EN ISO 12185

Pourpoint -51 CELSIUS ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In case of any problems, please request technical advice.



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailadress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

