



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailadress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL Motobike V-Twin 20W-50

Motobike V-Twin 20W-50 mineral is a mineral engine oil with selected additives for demanding 4-stroke motorcycles. It is characterized by high load capacity and reliability and is suitable for wet clutches. Motobike V-Twin 20W-50 mineral has excellent lubricating film adhesion and good shear stability as well as excellent cleaning properties and high ageing resistance.

Application note:

Motobike V-Twin 20W-50 mineral is suitable as engine oil for all motorcycles if the specification SAE 20W-50 JASO MA/MA2 is required. Especially suitable for use with air- or water-cooled V-engines with large displacement and high power. Particularly suitable for extremely high outside temperatures and use in racing.

Specifications:

Other specifications

Tried and tested in practice in units with filling regulations:

Cruiser motorcycles, Harley Davidson, V-TWIN Chopper

Properties:

Excellent cold start properties

High oxidation stability

Excellent shear stability

Very good detergent and dispersing properties



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

Very good viscosity-temperature behaviour

catalyst suitability

High safety reserves even under boundary lubrication conditions

Prevention of black sludge formation

Properties Data Unit Test according to

kinematic viscosity at 40°C 175,000 MM<sup>2</sup>/S DIN ISO 51562-2

Viscosity at 100°C 20.600 MM<sup>2</sup>/S DIN ISO 51562-2

Viscosity index 137 DIN ISO 2909

Colour Brown visual

Density at 15°C 880.0 KG/M<sup>3</sup> DIN EN ISO 12185

Pourpoint -33 CELSIUS ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In case of any problems, please request technical advice.



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

