

PRODUCT DATA SHEET



TIPP-OIL Combi Pro 5W-30

TIPP OIL Manufacturer GmbH Co. KG

Am Langen Kamp 2
59192 Bergkamen · Germany

Tel: (+49) 02307 9703274
Web: www.tippoil.com

Fax: (+49) 02307 9703275
E-Mail: contact@tippoil.com

Company registration number: HRA4299
VAT number: DE313987910

Revised on: 06.02.2025 | Number of the version: 03 | Replaces version: 01

Description of the

TIPP OIL Combi Pro 5W-30 is a synthetic low-friction engine oil for modern petrol and diesel cars, and diesel engines with and without turbocharging and direct injection.

TIPP OIL Combi Pro 5W-30 is a synthetic low-friction engine oil for modern petrol and diesel car engines with and without turbocharging and direct injection. TIPP OIL Combi Pro 5W-30 is characterised by minimised fuel consumption, offers excellent oil supply at cold start and ensures high wear and corrosion protection. Extended oil change intervals in accordance with the manufacturer's instructions.

Application notes

TIP OIL Combi Pro 5W-30 is ideally suited for energy-saving, year-round use in all modern petrol and diesel car engines. TIP OIL Combi Pro 5W-30 is ideally suited for energy-saving, year-round use in all modern petrol and diesel car engines. TIP OIL Combi Pro 5W-30 extends the service life of diesel particulate filters. The operating instructions of the vehicle and engine manufacturers must be observed.

Quality classification specifications:

- ACEA C3
- API SN

Recommendation:

- BMW Longlife-04
- MB 229.51/229.31
- VW 504 00 / 507 00
- Fiat 9.55535-S3
- Porsche C30

Properties:

- Excellent cold start properties
- Very stable and excellent viscosity behaviour even at high speeds
- High shear stability
- Fuel savings under all operating conditions
- Neutrality towards sealing materials
- Low evaporation tendency, therefore low oil consumption
- Catalyser suitability
- Extended oil change intervals protect natural resources

PRODUCT DATA SHEET



TIPP-OIL Combi Pro 5W-30

TIPP OIL Manufacturer GmbH Co. KG

Am Langen Kamp 2
59192 Bergkamen · Germany

Tel: (+49) 02307 9703274

Fax: (+49) 02307 9703275

Web: www.tippoil.com

E-Mail: contact@tippoil.com

Company registration number: HRA4299

VAT number: DE313987910

Revised on: 06.02.2025 | Number of the version: 03 | Replaces version: 01

Technical characteristics:

Eigenschaften	Daten	Einheit	Prüfung nach:
kinematic viscosity at 40°C	71,8	MM ² /S	DIN ISO 51562-2
kinematic viscosity at 100°C	12,1	MM ² /S	DIN ISO 51562-2
viscosity index	166		DIN ISO 2909
appearance	Yellow		
visuell density at 15°C	851	KG/M ³	DIN EN ISO 12185
Pour Point	-45	CELSIUS	ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations. To the best of our knowledge, all information corresponds to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of problems, please request technical advice.

25.10.2021 02:02:50