

# PRODUCT DATA SHEET



## TIPP-OIL FS Elite 5W-40

### TIPP OIL Manufacturer GmbH Co. KG

Am Langen Kamp 2  
59192 Bergkamen · Germany

Tel: (+49) 02307 9703274  
Web: [www.tippoil.com](http://www.tippoil.com)

Fax: (+49) 02307 9703275  
E-Mail: [contact@tippoil.com](mailto:contact@tippoil.com)

Company registration number: HRA4299  
VAT number: DE313987910

Revised on: 06.02.2025 | Number of the version: 03 | Replaces version: 01

### Description of the

TIPP OIL FS Elite 5W-40 is a synthetic low-friction engine oil for passenger car petrol and diesel engines with and without turbocharging and direct injection. TIPP OIL FS Elite 5W-40 is characterised by excellent cold-start properties, minimisation of fuel consumption, friction and wear. TIPP OIL FS Elite 5W-40 offers maximum operational reliability in all driving conditions, e.g. in extreme stop-and-go traffic in large cities, as well as when driving at high speeds on motorways.

### Application notes

TIPP OIL FS Elite 5W-40 is ideally suited for energy-saving, year-round use in modern petrol and diesel car engines. Extended oil change intervals according to manufacturer's instructions. The operating instructions of the vehicle and engine manufacturers must be observed.

### Quality classification specifications:

- API SN/CF
- ACEA A3-08/B4-08

### Recommendation:

- BMW Longlife-01
- MB 229.3/226.5
- Porsche A40
- Renault RN0700/0710
- VW 502 00/505 00
- Chrysler MS-10725/12991
- Fiat 9.55535-H2/M2/N2/Z2
- Opel GM-LL-B-025
- PSA B71 2296

### Properties:

- Excellent cold starting properties even at low temperatures
- Fuel savings under all operating conditions
- Very good detergent and dispersant properties
- Neutrality towards sealing materials
- Low evaporation tendency, therefore low oil consumption
- Extensive protection against wear, corrosion and foaming
- Extended oil change intervals protect natural resources

# PRODUCT DATA SHEET



## TIPP-OIL FS Elite 5W-40

**TIPP OIL Manufacturer GmbH Co. KG**

Am Langen Kamp 2  
59192 Bergkamen · Germany

Tel: (+49) 02307 9703274

Fax: (+49) 02307 9703275

Web: [www.tippoil.com](http://www.tippoil.com)

E-Mail: [contact@tippoil.com](mailto:contact@tippoil.com)

Company registration number: HRA4299

VAT number: DE313987910

Revised on: 06.02.2025 | Number of the version: 03 | Replaces version: 01

### Technical characteristics:

Eigenschaften	Daten	Einheit	Prüfung nach:
kinematic viscosity at 40°C	84,1	MM <sup>2</sup> /S	DIN ISO 51562-2
kinematic viscosity at 100°C	13,9	MM <sup>2</sup> /S	DIN ISO 51562-2
viscosity index	171		DIN ISO 2909
appearance	Yellow		
visuell density at 15°C	850	KG/M <sup>3</sup>	DIN EN ISO 12185
Pour Point	-42	CELSIUS	ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations. To the best of our knowledge, all information corresponds to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of problems, please request technical advice.

25.10.2021 02:02:50