

PRODUCT DATA SHEET



TIPP-OIL FS Supreme 10W-40

TIPP OIL Manufacturer GmbH Co. KG

Am Langen Kamp 2
59192 Bergkamen · Germany

Tel: (+49) 02307 9703274
Web: www.tippoil.com

Fax: (+49) 02307 9703275
E-Mail: contact@tippoil.com

Company registration number: HRA4299
VAT number: DE313987910

Revised on: 06.02.2025 | Number of the version: 03 | Replaces version: 01

Description of the

TIPP OIL FS Supreme 10W-40 is a synthetic high-performance low-friction engine oil for passenger car petrol and diesel engines with and without turbocharging and direct injection. Extended oil change intervals according to manufacturer's instructions. TIPP OIL FS 10W-40 is characterised by excellent cold-starting properties, minimisation of fuel consumption, friction and wear. With TIPP OIL FS 10W-40, a reliable and heavy-duty engine oil has been developed.

Application notes

TIPP OIL FS Supreme 10W-40 is ideally suited for year-round use in all modern petrol and diesel car engines. TIPP OIL FS Supreme 10W-40 is used in engines with the stated specifications. The operating instructions of the vehicle and engine manufacturers must be observed.

Quality classification specifications:

- API SL/CF
- ACEA A3/B4

Recommendation:

- BMW Special Oil
- Fiat 9.55535-G2/D2
- MB 229.1
- PSA B71 2294
- VW 501 01 / 505 00
- VW 502 00 / 500 00

Properties:

- Excellent cold starting properties even at low temperatures below -25°C
- Very stable and excellent viscosity behaviour, shear stability
- Fuel savings under all operating conditions
- Very good detergent and dispersant properties
- Neutrality towards sealing materials
- Low evaporation tendency, therefore low oil consumption
- Extensive protection against wear, corrosion and foaming
- Catalyser suitability
- Extended oil change intervals protect natural resources

PRODUCT DATA SHEET



TIPP-OIL FS Supreme 10W-40

TIPP OIL Manufacturer GmbH Co. KG

Am Langen Kamp 2
59192 Bergkamen · Germany

Tel: (+49) 02307 9703274

Fax: (+49) 02307 9703275

Web: www.tippoil.com

E-Mail: contact@tippoil.com

Company registration number: HRA4299

VAT number: DE313987910

Revised on: 06.02.2025 | Number of the version: 03 | Replaces version: 01

Technical characteristics:

Eigenschaften	Daten	Einheit	Prüfung nach:
kinematic viscosity at 40°C	94,4	MM ² /S	DIN ISO 51562-2
kinematic viscosity at 100°C	14,5	MM ² /S	DIN ISO 51562-2
viscosity index	160		DIN ISO 2909
appearance	Yellowbrown		
visuell density at 15°C	861	KG/M ³	DIN EN ISO 12185
Pour Point	-39	CELSIUS	ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations. To the best of our knowledge, all information corresponds to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of problems, please request technical advice.

25.10.2021 02:02:50