

PRODUCT DATA SHEET



TIPP-OIL LL Professional 0W-30

TIPP OIL Manufacturer GmbH Co. KG

Am Langen Kamp 2
59192 Bergkamen · Germany

Tel: (+49) 02307 9703274
Web: www.tippoil.com

Fax: (+49) 02307 9703275
E-Mail: contact@tippoil.com

Company registration number: HRA4299
VAT number: DE313987910

Revised on: 07.02.2025 | Number of the version: 03 | Replaces version: 01

Description of the

TIPP-OIL LL Professional 0W-30 is a synthetic low-friction engine oil for passenger car petrol and diesel engines with and without turbocharging and direct injection. Minimises friction, wear and fuel consumption, excellent cold starting properties. Extended oil change intervals in accordance with the manufacturer's instructions.

TIPP-OIL LL Professional 0W-30 extends the service life of the diesel particulate filter by reducing the concentration of ash-forming particles in the exhaust gas. Reduces the release of harmful emissions into the environment. Provides more safety through sustained high engine protection. Thanks to its formulation with special base oils, it achieves a high viscosity index.

Application notes

TIPP-OIL LL Professional 0W-30 is ideal for energy-saving, year-round use in modern petrol and diesel engines. TIPP-OIL LL Professional 0W-30 is suitable for extended oil change intervals and prolongs the service life of the particulate filter. The operating instructions of the vehicle and engine manufacturers must be observed.

Quality classification specifications:

- ACEA C3
- API SN

Recommendation:

- VW 504 00/507 00
- BMW Longlife-04
- Fiat 9.55535-S3
- MB 229.51/229.31
- Porsche C30

Properties:

- Excellent cold starting properties even at low temperatures of below -25°C
- Extremely stable and excellent viscosity behaviour, shear stability
- Fuel savings under all operating conditions
- Reliable lubricating film at high operating temperatures
- Neutrality towards sealing materials
- Low evaporation tendency, therefore low oil consumption
- Excellent protection against wear, corrosion and foaming
- Catalyser suitability
- Extended oil change intervals protect natural resources

PRODUCT DATA SHEET



TIPP-OIL LL Professional 0W-30

TIPP OIL Manufacturer GmbH Co. KG

Am Langen Kamp 2
59192 Bergkamen · Germany

Tel: (+49) 02307 9703274

Fax: (+49) 02307 9703275

Web: www.tippoil.com

E-Mail: contact@tippoil.com

Company registration number: HRA4299

VAT number: DE313987910

Revised on: 07.02.2025 | Number of the version: 03 | Replaces version: 01

Technical characteristics:

Eigenschaften	Daten	Einheit	Prüfung nach:
kinematic viscosity at 40°C	60,6	MM ² /S	DIN ISO 51562-2
kinematic viscosity at 100°C	11,8	MM ² /S	DIN ISO 51562-2
viscosity index	194		DIN ISO 2909
appearance	Yellowbrown		
visuell density at 15°C	845	KG/M ³	DIN EN ISO 12185
Pour Point	-48	CELSIUS	ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations. To the best of our knowledge, all information corresponds to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of problems, please request technical advice.

25.10.2021 02:02:50