

PRODUCT CERTIFICATE



TIPP-OIL DCT / DSG Super HC

TIPP OIL Manufacturer GmbH Co. KG

Am Langen Kamp 2
59192 Bergkamen · Germany

Tel: (+49) 02307 9703274

Web: www.tippoil.com

Fax: (+49) 02307 9703275

E-Mail: contact@tippoil.com

Company registration number: HRA4299

Sales tax identification number: DE331814405

Revised on: 19.03.2025 | Number of the version: 01 | Replaces version: 01

Description:

TIPP-OIL DCT / DSG Super HC is a synthetic transmission fluid for dual clutch transmissions. DCT / DSG Super HC guarantees stable lubrication behaviour even under extreme loads in midsummer and low winter temperatures. DCT / DSG Super HC enables practically slip-free operation and thus minimises torque losses. is made possible. DCT / DSG Super HC guarantees low wear and a long gearbox service life. service life of the transmission.

Instructions for use:

TIPP-OIL DCT / DSG Super HC has been specially developed for dual clutch transmissions of various car manufacturers such as Audi, BMW (Getrag), Citroen, Ford/Getrag, Mercedes Benz, Mitsubishi, Nissan, Peugeot, Porsche, Seat, Skoda, Volkswagen, Volvo.

Recommendation:

- BMW 83 22 0 440 214, BMW 83 22 2 147 477
- BMW 83 22 2 148 578, BMW 83 22 2 148 579
- Ford
- WSS M2C936 A
- MB 236.21 (001 989 85 03)
- MZ320065 Dia Queen SSTF I
- Peugeot/Citroen 9734.S2
- Porsche Oil No. 999.917.080.00
- VOLVO 1161838/1161839
- VW TL 052 182
- VW

Features & Benefits:

- Very good lubricity even at low temperatures in winter
- Low wear
- Excellent viscosity-temperature behaviour
- Outstanding protection against wear, corrosion and foaming
- Neutral behaviour towards sealing materials
- Stable lubricating film even under extreme loads in midsummer
- Very low pour point

PRODUCT CERTIFICATE



TIPP-OIL
DCT / DSG Super HC

TIPP OIL Manufacturer GmbH Co. KG

Am Langen Kamp 2
59192 Bergkamen · Germany

Tel: (+49) 02307 9703274

Fax: (+49) 02307 9703275

Web: www.tippoil.com

E-Mail: contact@tippoil.com

Company registration number: HRA4299

Sales tax identification number: DE331814405

Revised on: 19.03.2025 | Number of the version: 01 | Replaces version: 01

Technical specifications:

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	7,4	MM ² /S	DIN ISO 51562-2
viscosity index	177		DIN ISO 2909
appearance	Yellowbrown		VISUELL
density at 15°C	846	KG/M ³	DIN EN ISO 12185
Pour Point	-48	°C	ASTM D 7346

All declared values are approximate and subject to standard production variations. To the best of our knowledge all information reflects the current state of findings and our development.

Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician. 26.07.2024 02:00:00