

PRODUCT CERTIFICATE



TIPP-OIL HLPD 15

TIPP OIL Manufacturer GmbH Co. KG

Am Langen Kamp 2
59192 Bergkamen · Germany

Tel: (+49) 02307 9703274
Web: www.tippoil.com

Fax: (+49) 02307 9703275
E-Mail: contact@tippoil.com

Company registration number: HRA4299
Sales tax identification number: DE331814405

Revised on: 14.03.2025 | Number of the version: 01 | Replaces version: 01

Description:

Tipp-Oil HLPD 15 is a detergent hydraulic oil and therefore has a high wetting and cleaning effect. It is designed on the basis of selected base oils with additives to prevent corrosion, wear and friction. HLPD 15 also contains dispersing and detergent agents that ensure clean hydraulics at all times.

These additives dissolve impurities, keep them in suspension and thus enable the cleaning of contaminated hydraulic systems. The functional elements of a hydraulic system thus remain free of deposits and adhesions. Penetrating quantities of water are emulsified and the trouble-free operation of the hydraulic system is guaranteed.

Instructions for use:

Tipp-Oil HLPD 15 is used in hydraulic systems, in agriculture, construction machinery, cement factories, foundries, electric multi-plate clutches, as a functional test oil, as a running-in oil for units and machines, in textile machines and in machine tools. HLPD 15 exceeds the requirements for hydraulic oils HLP according to DIN 51 524 Part 2 for hydraulic systems.

Specification:

- DIN 51524-2
- ISO 6743-4 HM *except demulsibility

Recommendation:

- Daimler Chrysler DBL 6721

Features & Benefits:

- High ageing resistance
- Good air separation capacity
- Neutrality towards sealing materials
- Ash and zinc-free
- Extensive protection against wear, corrosion and foaming
- Very stable and excellent viscosity and temperature behaviour
- Excellent detergent and dispersing properties
- Excellent corrosion protection, even when absorbing moisture

PRODUCT CERTIFICATE



TIPP OIL Manufacturer GmbH Co. KG

Am Langen Kamp 2
59192 Bergkamen · Germany

Tel: (+49) 02307 9703274
Web: www.tippoil.com

Fax: (+49) 02307 9703275
E-Mail: contact@tippoil.com

Company registration number: HRA4299
Sales tax identification number: DE331814405

Revised on: 14.03.2025 | Number of the version: 01 | Replaces version: 01

TIPP-OIL
HLPD 15

Technical specifications:

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	15,0	MM ² /S	DIN ISO 51562-2
kinematic viscosity at 100°C	3,5	MM ² /S	DIN ISO 51562-2
viscosity index	115		DIN ISO 2909
appearance	Yellow		VISUELL
density at 15°C	842	KG/M ³	DIN EN ISO 12185
Pour Point	-45	°C	ASTM D 7346

All declared values are approximate and subject to standard production variations. To the best of our knowledge all information reflects the current state of findings and our development.

Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician. 26.07.2024 02:00:00