

PRODUCT CERTIFICATE



TIPP-OIL
HSS SHPD 15W-40

TIPP OIL Manufacturer GmbH Co. KG

Am Langen Kamp 2
59192 Bergkamen · Germany

Tel: (+49) 02307 9703274
Web: www.tippoil.com

Fax: (+49) 02307 9703275
E-Mail: contact@tippoil.com

Company registration number: HRA4299
Sales tax identification number: DE331814405

Revised on: 18.03.2025 | Number of the version: 01 | Replaces version: 01

Description:

Tipp Oil HSS SHPD 15W-40 is a high-quality SHPD multigrade engine oil for passenger car and lorry diesel engines diesel engines with and without turbocharging of all makes. It can be used all year round for all engines. Minimises friction, wear and fuel consumption, excellent cold start properties. cold starting properties. HSS SHPD 15W-40 enables extended oil change intervals in accordance with manufacturer's instructions.

Instructions for use:

TIPP-OIL HSS SHPD 15W-40 is used in mixed fleets in engines with the stated specifications. specifications. It is particularly suitable for modern diesel vehicles that fulfil the Euro V emission standard. The operating instructions of the vehicle and engine manufacturers must be must be observed.

Specification:

- API CI-4/SL
- ACEA E7

Recommendation:

- Deutz DQC III-10
- Mack EO-N
- MAN M 3275-1
- MB 228.3
- MTU Typ 2
- Renault VI RLD-2
- VOLVO VDS-3

Features & Benefits:

- Very stable and excellent viscosity behaviour
- Excellent ageing resistance
- Best suitability for difficult operating conditions
- High oxidation stability and high pressure absorption capacity
- High safety reserves even under extreme lubrication conditions
- Protection of natural resources through extended oil change intervals

PRODUCT CERTIFICATE



TIPP-OIL
HSS SHPD 15W-40

TIPP OIL Manufacturer GmbH Co. KG

Am Langen Kamp 2
59192 Bergkamen · Germany

Tel: (+49) 02307 9703274

Fax: (+49) 02307 9703275

Web: www.tippoil.com

E-Mail: contact@tippoil.com

Company registration number: HRA4299

Sales tax identification number: DE331814405

Revised on: 18.03.2025 | Number of the version: 01 | Replaces version: 01

Technical specifications:

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	109,1	MM ² /S	DIN ISO 51562-2
kinematic viscosity at 100°C	15,9	MM ² /S	DIN ISO 51562-2
viscosity index	155		DIN ISO 2909
appearance	Yellowbrown		VISUELL
density at 15°C	870	KG/M ³	DIN EN ISO 12185
Pour Point	-42	°C	ASTM D 7346

All declared values are approximate and subject to standard production variations. To the best of our knowledge all information reflects the current state of findings and our development.

Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician. 26.07.2024 02:00:00