

PRODUCT DATA SHEET



TIPP OIL Mineral Hydraulic HLP 220

TIPP OIL Manufacturer GmbH Co. KG

Am Langen Kamp 2
59192 Bergkamen · Germany

Tel: (+49) 02307 9703274

Web: www.tippoil.com

Fax: (+49) 02307 9703275

E-Mail: contact@tippoil.com

Company registration number: HRA4299

VAT number: DE313987910

Revised on: 14.04.2025 | Number of the version: 01 | Replaces version: 01

Description of the

Tipp Oil Mineral Hydraulic HLP 220 is an optimally alloyed hydraulic oil. It has a high performance level and a wide range of applications throughout the industry. Mineral Hydraulic HLP 220 offers excellent wear protection under extreme loads. Mineral Hydraulic HLP 220 is characterised in particular by good viscosity-temperature behaviour, high ageing resistance and reliable corrosion protection.

Application notes

Tipp Oil Mineral Hydraulic HLP 220 can be used universally in all hydraulic systems. The operating instructions of the vehicle and engine manufacturers must be observed.

Quality classification specifications:

- DIN 51506 VC
- DIN 51506, Teil 2

Recommendation:

- AFNOR NF E 48-603 (HM, HV)
- ISO 6743/4 HV

Properties:

- High performance level
- High ageing resistance
- Reliable corrosion protection
- Very good viscosity-temperature behaviour
- Excellent wear protection
- Neutral towards sealing materials

PRODUCT DATA SHEET



TIPP OIL Mineral Hydraulic HLP 220

TIPP OIL Manufacturer GmbH Co. KG

Am Langen Kamp 2
59192 Bergkamen · Germany

Tel: (+49) 02307 9703274
Web: www.tippoil.com

Fax: (+49) 02307 9703275
E-Mail: contact@tippoil.com

Company registration number: HRA4299
VAT number: DE313987910

Revised on: 14.04.2025 | Number of the version: 01 | Replaces version: 01

Technical characteristics:

Eigenschaften	Daten	Einheit	Prüfung nach:
kinematic viscosity at 40°C	237,0	MM²/S	DIN ISO 51562-2
kinematic viscosity at 100°C	16,6	MM²/S	DIN ISO 51562-2
viscosity index	92		DIN ISO 2909
appearance	Yellow		
visuell density at 15°C	897	KG/M³	DIN EN ISO 12185
Pour Point	-12	CELSIUS	ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations. To the best of our knowledge, all information corresponds to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of problems, please request technical advice.
26.07.2024 04:52:00